

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
24 December 2003 (24.12.2003)

PCT

(10) International Publication Number
WO 03/106065 A1

(51) International Patent Classification⁷: **B21D 5/02**,
G05B 19/4093

(FI). VÄISÄNEN, Martti [FI/FI]: Korpisaarentie 15,
FIN-61410 Ylistaro (FI).

(21) International Application Number: PCT/FI03/00464

(74) Agent: **TAMPEREEN PATENTTITOIMISTO OY**;
Hermiankatu 12 B, FIN-33720 Tampere (FI).

(22) International Filing Date: 12 June 2003 (12.06.2003)

(25) Filing Language: Finnish

(26) Publication Language: English

(30) Priority Data:
20021155 14 June 2002 (14.06.2002) FI

(71) Applicant (for all designated States except US): **FINN-
POWER OY** [FI/FI]; Metallitie 4, FIN-62200 Kauhava
(FI).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **IRRI, An-
tero** [FI/FI]; Vuorenkiventie 2, FIN-35700 Vilppula

(81) Designated States (national): AE, AG, AL, AM, AT (util-
ity model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA,
CH, CN, CO, CR, CU, CZ (utility model), DE (util-
ity model), DK, DK (utility model), DK, DM, DZ, EC, EE
(utility model), EE, ES, FI (utility model), FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KH, KG, KP, KR, KZ,
LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU,
SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GI, GM,
KE, LS, MW, MZ, SD, SI, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

[Continued on next page]

(54) Title: A METHOD IN THE CONTROL OF A MACHINE TOOL CELL



(57) Abstract: The invention relates to a method for controlling a machine tool cell consisting of a press brake (6) and one or more robots (9) serving the same. According to the invention, the data needed for designing the movement plan (200), or the like, for the robot (9) is collected in connection with designing the bending program (100) for the press brake (6), and said data is automatically compiled to a bend line table (BLT), which table indicates, for bendings to which a sheet is subjected in the press brake (6), the bend lines and their locations and positions in a coordinate system (X, Y, Z), whose origin is the sheet centre (AKP) of the sheet to be machined. Said bend line table (BLT) is further set to be used as a variable in movement programs (200) for one or more robots (9) serving the press brake (6). When the bending program (100) of the press brake (6) is changed for a new product, it is also easy and fast, by means of the invention, to generate a new movement program (200) of the robot (9) for the new product.

WO 03/106065 A1